

SKN3507

Total Transfer Security label



PRODUCT DESCRIPTION

Traces of prints or patterns are totally transferred to substrates when the tape is removed. Excellent tamper evident performances.

TYPICAL APPLICATIONS

Suitable to be die-cut into labels for use on paper materials with varnishing.

SIZE

48~480mm, length: 30~500m

TECHNICAL DATA

180° Peel Adhesive for VOID:

0.20~0.98N/2,5cm *PSTC-1*

Total Thickness: 0.06~0.07mm

Initial Tack: < 10cm *PSTC-6 #14 ball*

Holding Power: 1.0kg/25mm x 25mm :

>24hrs *PSTC-7*

Holding Power for temperature resist

80°C: 0.5kg/25mm x 25mm :

>24hrs *PSTC-7*

COLOR

Clear

LINER

White double PE single silicon glassine paper

CARRIER

PET

VOID TEMPERATURE

Temperature: -10°C ~ +40°C;

Relative humidity: 55% +/-10%

RECOMMENDED OPERATION

TEMPERATURE

+10°C ~ +35°C

VOID MESSAGE

Standard VOID print

PERSONALISED VOID MESSAGE

Subject to discussion

ADDITIONAL PRINTING

Available upon request, sequential numbering, bar codes etc.

AVAILABLE FORMATS

Jumbo rolls, log rolls, slit rolls, die cuts on roll.

SHELF LIFE

1 year under normal condition. Avoid exposing to high humidity and direct sunlight.

HOW TO APPLY

When applying the tape the surfaces to be bonded should be dry, dust & grease free and thoroughly clean. Avoid touching the exposed adhesive surface of the tape as this impairs the performance. The adhesive used on these tapes are pressure sensitive, so always ensure sufficient pressure is applied to the tape evenly over the whole surface to ensure the best bonding results.

Multifoil products are produced under stringent manufacturing process and quality control conditions. The information and typical values provided are based upon research believed to be reliable and are provided without guarantee and do not constitute a warranty. Purchasers should determine the suitability of the products prior to its intended use.

Product liability – Terms of sale – article 8

Version August 2014

